

UltraDynamics®

Series 8102-VM UV System

Vertical Closed Vessel

The UltraDynamics® Series 8102-VM UV System design is the result of over 50 years of experience in the application of UV for the treatment of water and wastewater. The Series 8102-VM has been proven effective in a number of global installations over a broad range of applications. Each Series 8102-VM system provides a dose of 30,000 to 400,000 micro-watt seconds per square centimeter at a wavelength of 254nm ultraviolet energy for deactivation of microorganisms.

The germicidal lamps are guaranteed for 9,000 hours of continuous operation. The pure, fused quartz sleeves used to protect the lamps are manufactured to provide a maximum transmission of UV energy.

All UltraDynamics® UV systems are supplied with a variety of standard design features and an assortment of optional features to help meet your specific application needs.

Features:

- ◆ 316LSS stainless steel construction
- ◆ Electro polished and passivated
- ◆ Pressure drop <1 PSIG at peak rated flow
- ◆ Maximum operating pressure 150 PSIG
- ◆ Remote power supply for maximum flexibility of installation.
- ◆ Drain and monitor sight port included



Options:

- ◆ Remote alarm capability
- ◆ Quartz sleeve cleaning system
- ◆ High Temperature cut off switch (Thermistor type)
- ◆ Narrowband germicidal UV monitor senses over 90% 254 nanometer germicidal wave length
- ◆ 1/4" sample port on inlet and outlet
- ◆ (L.O.W.) Lamp out warning system
- ◆ UL Certification available
- ◆ Available in flanged, threaded or sanitary process connections
- ◆ Available with 185nm ozone producing lamps or high output lamps



Model No.	CAPACITY GPM m ³ /hr)		Potable Water (40 mJ/cm ² 90%T	High Purity Water	Inlet/Outlet Size	KW		AMPS		DIMENSIONS	Shipping Weight	No. of Lamps	Lamp Length in (mm)
	Clear Waste Water					120V	220V	120V	220V				
8102-VM-15	12 (2.7)	20 (4.5)	24 (5.5)	1.5" NPT	0.16	0.14	1.3	0.6	40 x 7 x 14 (1016 x 180 x 356)	60 LBS 27 KGS	2	36 (914)	
8102-VM-20	35 (8)	50 (11)	60 (14)	2" NPT	0.26	0.25	2.1	1.1	40 x 14 x 12 (1016 x 356 x 305)	150 LBS 68 KGS	4	36 (914)	
8102-VM-35	50 (11)	55 (15)	80 (18)	2" NPT	0.39	0.38	3.2	1.7	40 x 14 x 12 (1016 x 356 x 305)	225 LBS 102 KGS	6	36 (914)	
8102-VM-80	55 (12.5)	90 (20)	110 (25)	2" NPT	0.54	0.54	4.5	2.5	40 x 14 x 12 (1016 x 356 x 305)	225 LBS 102 KGS	8	36 (914)	
8102-VM-40L	70 (16)	90 (20)	110 (25)	3" FLG	0.38	0.36	3.2	1.7	72.5 x 14 x 14 (1842 x 356 x 356)	325 LBS 147 KGS	4	64 (1626)	
8102-VM-60L	100 (23)	130 (30)	160 (36)	3" FLG	0.57	0.54	4.8	2.5	72.5 x 14 x 14 (1842 x 356 x 356)	350 LBS 159 KGS	6	64 (1626)	
8102-VM-80L	130 (30)	175 (40)	220 (50)	3" FLG	0.76	0.72	6.4	3.4	72.5 x 14 x 14 (1842 x 356 x 356)	500 LBS 227 KGS	8	64 (1626)	

APPLICATIONS

BACTERIA-FREE WATER FOR PROCESSING

- ◆ Breweries
- ◆ Cosmetics
- ◆ Pharmacy
- ◆ Chemical Plants
- ◆ Distilleries
- ◆ Bottling Plants

DI SYSTEMS

- ◆ Prevent microorganism growth in resin beds.
- ◆ TOC reduction

DRINKING WATER SYSTEMS

- ◆ Controls bacteria in potable water supplies

ELECTRONICS

- ◆ Deactivates microorganisms in photomask & micro-electronics rinse water loops
- ◆ For reduction of TOC levels in ultra pure water.

FISH HATCHERIES

- ◆ Prevents "Whirling Disease"
- ◆ Destroys fungus
- ◆ Reduces egg mortality

SEWAGE EFFLUENT

- ◆ Final disinfection

MARINE INDUSTRIES

- ◆ Disinfection of process and potable water systems
- ◆ Offshore drilling platforms

REVERSE OSMOSIS SYSTEMS

- ◆ Pre-bacterial control which helps to extend membrane life
- ◆ Post-storage tank disinfection

SWIMMING POOLS AND SPAS

- ◆ Algae & chlorine resistant bacteria control
- ◆ Reduces need for chemical additives

Warranty and Capability

Severn Trent Services UltraDynamics® Ultraviolet Disinfection products are warranted for eighteen months from the date of invoice, or twelve months from the date of installation, whichever is earlier.

Disinfection technologies, water quality monitors and instrumentation for water and wastewater are areas of specialization. Over 35 years of industrial and municipal application experience in the water and wastewater industries.

Brief Specification

The Ultraviolet Disinfection System shall incorporate low pressure, germicidal UV lamps positioned in a stainless steel chamber.

The system shall include UV lamps, protective quartz sleeves and a power supply center rated at (120Vac, 50/60Hz) (220Vac, 50/60Hz).

UV lamps shall be slimline, low pressure mercury vapor, hot cathode, instant start design and shall produce ultraviolet light with a minimum of 90% of emissions within the wavelengths of 233.7 and 273.7nm. Lamps shall be field replaceable by plant operations and maintenance personnel and shall be guaranteed for a period of 1 year. Lamp sleeves shall be manufactured from General Electric type 214 clear fused quartz. Sleeves shall be circular with open end fire polished smooth. Quartz sleeves shall be rated for UV transmittance of 89% and shall be subject to minimal solarization. An optional automatic (manual) sleeve cleaning system can be incorporated.

The UV system shall be an UltraDynamics® Series 8102-VM as manufactured by UltraDynamics®.

Severn Trent Services

3000 Advance Lane

Colmar, PA 18915

Telephone 215 997 4000

Fax 215 997 4062

marketing@severntrentservices.com

165.0090.1 04/04